

caratteristiche tecniche produzione motocicli 1984

	125MCW	125F5W	125X1 enduro	250MCW	250F5W	350F5	350F4T	350HW enduro	496MC	560F4T regolarità
MOTORE	Rotax 2T	Rotax 2T	Rotax 2T	Rotax 2T	Rotax 2T	Rotax 2T	Rotax 4T	Rotax 4T	Rotax 2T	Rotax 4T
numero cilindri	1	1	1	1	1	1	1	1	1	1
alesaggio e corsa	54x54	54x54	54x54	72x61	72x61	82x66	79.5x70.4	79.5x70.4	85x87	94x81
cilindrata in cc.	123.7	123.7	123.7	248.3	248.3	348.3	349	349	493	561.8
rapporto di compressione	15.5	15	10	14.5	14.5	13	9.2	9.2	12.2	9.2
potenza max.	30/11500	30/10900	18.5/7800	42/9200	42/9200	42/9200	36	36	62/8200	42
cambio	6V.	6V.	6V.	5V.	5V.	5V.	5V.	5V.	4V.	5V.
carburatore	Ø 34	Ø 34	Ø 32	Ø 34	Ø 34	Ø 36	Ø 36	Ø 36	Ø 40	Ø 38
accensione	Motoplatt	Motoplatt	Bosch	Bosch	Bosch	Bosch	Nippondenso	Nippondenso	Bosch	Nippondenso
TELAIO	Frigerio	Frigerio	Frigerio	Frigerio	Frigerio	Frigerio	Frigerio	Frigerio	Frigerio	Frigerio
sospensione anteriore in mm.	Ø 38	Ø 38	Ø 35	Ø 40	Ø 40	Ø 40	Ø 40	Ø 38	Ø 40	Ø 40
sospensione posteriore	mono	mono	2 ammort.	mono	mono	mono	mono	mono	mono	mono
freno anteriore	Ø 125	Ø 125	Ø 140	Ø 140	Ø 140	Ø 140	disco	disco	Ø 140	disco
freno posteriore	Ø 125	Ø 125	Ø 125	Ø 160	Ø 160	Ø 160	Ø 160	Ø 160	Ø 160	Ø 160
pneumatico anteriore	3.00x21	3.00x21	3.00x21	3.00x21	3.00x21	3.00x21	3.00x21	3.00x21	3.00x21	3.25x21
pneumatico posteriore	4.00x18	4.00x18	4.00x18	4.50x18	4.50x18	4.50x18	4.50x18	4.00x18	4.50x18	4.50x18
PESI, MISURE E PRESTAZIONI										
peso a secco in kg.	94	96	100	98	102	102	137	135	104	137
interasse in mm.	1510	1440	1400	1460	1460	1460	1480	1420	1480	1480
lunghezza totale in mm.	2130	2130	2000	2150	2150	2150	2150	2100	2150	2150
larghezza max. in mm.	860	860	860	860	860	860	860	860	860	860
altezza sella in mm.	970	970	860	980	980	980	900	860	900	900
altezza minima da terra in mm.	390	390	310	390	390	390	380	300	380	380
capacità serbatoio in litri	9.2	8.2	10	8.2	9.2	9.2	10	10	9	10
velocità max. in km/h	—	110	125	—	120	120	130	130	—	140



FRIGERIO s.r.l.
24047 Treviglio (Bg)
Via Canonica, 79
Tel. 0363/47.133-4-5



serie 84

Enduro - Cross - Regolarità



350 HW

125 X1



125 F5 W



125 MCW



250 MCW





250F5W



350F5



496MC



560F4T

